




redphephrele

date	09/02/2015	designer	Lyndsay
job name & no.	0026727_Tridan_Caustic Soda_Label_500g	version number	V5
product	Tridan Caustic Soda_500g Label	date created	04/11/2014
job size	272,97(w) x 40(h)mm		
colours/finishing	 BLACK	 PANTONE 1815 C	

272,97mm

40mm



WARNINGS: DO NOT EXCEED RECOMMENDED DOSAGE. Handle with care. Corrosive and can cause burns. Keep out of reach of children and keep lid tightly secured. Wear appropriate personal protecting equipment. Avoid all contact with the eyes, skin and clothing. Do not ingest. Avoid breathing in any fumes. Fumes could be flammable. Do not use on aluminium, soft plastic or fibreglass surfaces. Do not use in combination with any other drain cleaners, plungers or aerosols. Contact with acids liberates toxic gas.

PRECAUTIONS: Store, tightly sealed, in a cool dry place. Dispose of empty container in a safe place.

FIRST AID: Following skin or eye contact, flush well with water. If ingested, drink 3-4 glasses of water and consult your doctor immediately. Do not induce vomiting.

TRIDAN® CAUSTIC SODA

DANGEROUS • POISONOUS • CORROSIVE



Contains Caustic Soda (sodium hydroxide). Keep out of reach of children.

Uses for TRIDAN® CAUSTIC SODA

- 1. Cleaning Greasy Dishes and Cement Floors.** Slowly add 125g to 5 litres cold water. Soak, scrub and rinse well. Not suitable for aluminium surfaces.
- 2. Removing Old Paint.** Slowly add 125g to 5 litres cold water. Soak, scrub and rinse well.
- 3. Unblocking Drains.** Pour 3-4 tablespoons into outside drain hole, followed by cold water. (3 Heaped tablespoons for inside drains - 60g)

500 g

Model Product Distributors (Pty) Ltd.
Co. Reg. No. 1991/005938/07.

PO Box 293 Modderfontein, 1645

Tel: 011 997 3400 or 08600 MODEL (66335).
Email: info@modelproducts.co.za